



ACT-3000

ACT-3000 is built with a stainless steel chassis with all controls easily accessible on the unit's side. The ozone generator has built-in monitoring of all vital parameters and shuts down the unit in case of any errors. The unit can also be controlled manually 0-100% using the power knob, or via the built-in digital input or the built-in 4-20 mA input.

ACT-3000 is used for confined spaces with odor problems or sanitation needs, such as garbage rooms, fire sanitation or sanitation of other enclosed spaces.

Option (not included): lockable wall-mount bracket.



TECHNICAL SPECIFICATION

Ozone production	
Production	0 - 350 mg/h
Feed gas (air)	
Quality	Technically clean air [21% O ₂]
Filter class	F-7
Fan capacity, max	47 m ³ /h
Ambient conditions	
Temperature	0 to +40 °C (+32 to +104 °F)
Humidity, max	85 % (R. H.) Non-condensing
Power supply	
Voltage rating	230 VAC, 50 Hz
- optional	115 VAC, 60 Hz
Power consumption, max	18 W
Dimensions	
Size (H x W x D)	225 x 101 x 80 mm (8.9 x 4 x 3.1 in)
Weight	2 kg (4.4 lbs)
IP class	20
Option (not included)	Stainless steel lockable wall-mount bracket

ADVANTAGES

- Stainless steel cabinet
- Very low noise level
- Adjustable ozone production (0-100%)
- Compact design
- Easy to maintain
- Built-in digital input
- Built-in 4-20 mA input

