

Closed cooling  
system

Elektravägen 53  
SE-126 30 Hägersten, Sweden  
+46 10 252 30 00  
www.ozonetech.com

# WENR003s

The WENR003s closed cooling system is a high-efficiency fully automatic cooling system delivered complete with circulation pump. The unit is suitable for applications where external cooling source is not available, or if eg. cost of using tapwater is too high.



## Technical specification

<b>Cooling capacity</b>	3.4 kW
Output water temp.	+7°C at max 35°C
<b>Circulation pump</b>	
Flow	20 L/min @ 2,1 bar g
Tank (semi-closed)	40 L
Enclosure	Galvanized, painted RAL7035
Refrigerant	R410A
<b>Ambient conditions</b>	
Temperature	0 - 40°C
Humidity, max	75 % (R. H.) Non-condensing
<b>Electrical connections</b>	
Voltage rating	1-phase, 230 VAC, 50 Hz + PE
Power consumption	1.8 kW
<b>Dimensions</b>	
Size (W x D x H)	655 x 600 x 1,035 mm (25.8x23.6x40.7 in)
Weight (empty tank)	90 kg (199 lbs)

## Advantages

- Fully automatic for easy operation
- Built-in circulation pump
- Flow control protection
- High pressure protection
- Microprocessor controlled incl. temperature control & sensors

Unless otherwise specifically stated in writing, NL 09 general terms for sales and delivery always apply. See [www.teknikforetagen.se](http://www.teknikforetagen.se) or contact us for a copy.



© Ozonetech

**ozonetech.**  
a MELLIFIQ brand